Dynasty® LED Omni Light 802B Series











5 Year Warranty

Specifications

Model	802B-27W	
Power Consumption	≤28W	
Input Voltage	AC100-277V 50-60Hz	
CCT*	3000K / 4000K / 5000 K	
Power Factor	≥0.9	
CRI	>80	
Lumen	3440 ±173 lm	
LED	Samsung	
LED Quantity	0.3W x 81 LEDs	
LED LM80	Yes	

^{*} Other CCTs available upon request.

Beam Spread

Model	802B-27W	
Power Consumption	≤28W	
Input Voltage	AC100-277V 50-60Hz	
CCT*	3000K / 4000K / 5000 K	
Power Factor	≥0.9	
CRI	>80	
Lumen	3440 ±173 lm	
LED	Samsung	
LED Quantity	0.3W x 81 LEDs	
LEDIMOO	Vas	



Samsung

LEDs



Rubycon

Capicators




E26/E39/EX39

Base



JAE Connectors

Dimensions





1350 cd/klm co - c180



Lifespan of 10 years



Reliability Test



Surge Protection Circuit



Environmentally Friendly



Savings of 87% on **Electrical Costs**



Suitable for **Enclosed Fixtures**



 $\eta = 100\%$

135°

120


Omni Directional



Dynasty® LED Omni Light 802B Series



Typical Installation




High Bay Lighting

Maximum Rating

Parameter	Rating	Units
Aluminum Heat Sink Temperature	58.2	С
Operating Temperature	-20~+65	С
Storage Temperature	-40~+80	С
Equilibrium Temperature	25	С

Street Lighting / Acorn


Wiring Diagram



LED Omni Light Wiring Diagram

Product Packing Specification

Packing Details		
Pack Quantity	12pcs	
Net Weight	1.8lbs/797.4g	
Gross Weight Per CTN	24lbs/10.9kg	
Box Size	4.96*4.96*10" 126*126*255mm	
CTN Size	16.1*11*20.9" 400*270*530mm	







! CAUTIONS

- Do not place lamp near flammable materials.
- Please allow lamp to cool before replacing.

